

LEISTER

PROCESS HEAT

Matsu VietNam

Tel: 028 6679 4137

Hp: 09357 08198

E: matsuvn.contact@gmail.com

info@matsu-vn.com

Hot air blower

➔ **HOTWIND PREMIUM
HOTWIND SYSTEM**



New!

The new HOTWIND PREMIUM and HOTWIND SYSTEM from Leister

The new HOTWIND PREMIUM is the successor to the hugely popular HOTWIND S. Its brushless motor ensures that this hot air blower has a long service life. The maximum air volume can now be set steplessly up to 900 l/min via the potentiometer.

The wide range of applications makes the new HOTWIND SYSTEM truly impressive: be it as a unit with integrated control or as a unit for integration in a closed loop control circuit using a system interface.

Advantages



1		Infinitely adjustable: Potentiometers for stepless adjustment of the heating and blower (PREMIUM and SYSTEM).
2		Remote controlled: Interface with alarm contact in the HOTWIND SYSTEM for controlling the air volume and heat output, using 4 – 20 [mA] or 0 – 10 [V] signal.
3		Integrated: Temperature probe in the HOTWIND SYSTEM for even greater precision.
4		User friendly: Display on the HOTWIND SYSTEM provides the user with status information.
5		Cleverly combined: Main switch with integral function button for programming (SYSTEM).
6		Cool: The unit is automatically cooled prior to switching off by pressing the function button.

Technical features

	PREMIUM	SYSTEM
Heat output and air volume steplessly adjustable with potentiometer	•	•
Integrated power electronics	•	•
Protection against heating element or device overheating	•	•
Brushless blower motor	•	•
Alarm output		•
Integrated temperature control		•
Remote control interface for temperature or power set point		•
Remote control interface for air volume adjustment		•
Integrated temperature probe		•
Display for showing the setpoint and actual values (°C or °F)		•



HOTWIND SYSTEM with wide slot nozzle integrated in a blow-off application.



HOTWIND SYSTEM as hot air provider in a shrinking process.

Technical data

Voltage	V~	120	230	230	230	230	400
Power consumption	W	2300	2300	2300	3100	3700	5400
Frequency	Hz	50/60					
Max. air outlet temperature	°C	650	650	650	800	650	650
Max. air flow (20 °C)	l/min.	200 – 900					
Static pressure	Pa	500					
Noise emission	L _{pA} (dB)	< 70					
Weight without cable	kg	2.6					
Measure		see below					
Mark of conformity		CE					
Certification scheme		CCA					
Protection classe II		□					
Without connecting plug		•		•			•
Connecting plug (Euro)			•		•		
Art. No. PREMIUM		140.095	142.612	142.643	142.608	142.609	140.098 142.644
Art. No. SYSTEM		142.636	142.646	140.096		142.645	142.640 142.641

Subject to change without notice
Connection voltage non-switchable

Additional versions on request

All devices available by August
Exept 400 V (Dez)

Accessories HOTWIND

107.262		Wide slot nozzle, push-fit, 300 × 4 mm (Other sizes available)
105.919		Tubular nozzle, push-fit, 456 × 306 × 3 mm (Other sizes available)
107.329		Sieve reflector, push-fit, 76 × 75 mm (Other sizes available)
106.174		Shell reflector, push-fit, 400 × 65 mm (Other sizes available)
107.245		Round nozzle, push-fit, Ø 40 mm (Other sizes available)
107.335		Sieve reflector, push-fit, Ø 150 mm (Other sizes available)
141.723		Handtool-Kit (Handle and protective tube)
106.956		Thermocouple with plug, 1 m cable



Application as a handheld or table unit with handle and protective tube.

Installation dimensions in mm

